

AENOR

AENOR Product Certificate



B78/000001

AENOR certifies that the organization

RTR ENERGIA, S.L.

registered office PI LA ESTACIÓN, CL GAVILANES, 11 28320 PINTO (Madrid - Spain)

supplies Capacitors for power factor compensation

in compliance with EN 60831-1:2014 (IEC 60831-1:2014)
EN 60831-2:2014 (IEC 60831-2:2014)

References Specified in Annex to the Certificate

Production site Cl GAVILANES, 11 - Pg IND LA ESTACIÓN 28320 PINTO (Madrid - Spain)

Certification scheme In order to grant this Certificate, AENOR has tested the product and has verified the quality system implemented for its manufacture. AENOR performs these tasks periodically while the Certificate has not been cancelled, in accordance with Specific Rules RP B78.01.

This certificate supersedes B78/000001, dated 2017-06-19

First issued on 2015-07-01
Modified on 2021-05-25
Validity date 2026-05-20

Rafael GARCÍA MEIRO
Chief Executive Officer

AENOR

AENOR Product Certificate

B78/000001

Annex to Certificate

Reference	Trade Mark	Single-phase / three-phase; unit / bank	Rated voltage and frequency	Rated reactive power; capacitance tolerance	Temperature category	Disconnecter (by overpressure / thermal)	Further data
DWCAP RCT	RTR	Trifásico; unitario, filtro armónicos Three-phase; unit capacitor, harmonics filter	Max. 525 V-; 50/60 Hz	Max. 35 kVAR; -5% +15%	-25/D	Incluido; por sobrepresión Included; by overpressure	Nivel de aislamiento: 5/12 kV; resistencia interna de descarga; uso interior; conexión por bornes Insulating level: 5/12 kV; internal discharge resistor; indoor use; terminals connection
DWCAP RTF	RTR	Trifásico; unitario, reforzado Three-phase; unit capacitor, reinforced	Max. 525 V-; 50/60 Hz	Max. 35 kVAR; -5% +15%	-25/D	Incluido; por sobrepresión Included; by overpressure	Nivel de aislamiento: 5/12 kV; resistencia interna de descarga; uso interior; conexión por bornes Insulating level: 5/12 kV; internal discharge resistor; indoor use; terminals connection
DWCAP	RTR	Trifásico; unitario Three-phase; unit capacitor	Max. 525 V-; 50/60 Hz	Max. 35 kVAR; -5% +15%	-25/D	Incluido; por sobrepresión Included; by overpressure	Nivel de aislamiento: 5/12 kV; resistencia interna de descarga; uso interior; conexión por bornes Insulating level: 5/12 kV; internal discharge resistor; indoor use; terminals connection

First issued on 2015-07-01
Modified on 2021-05-25
Validity date 2026-05-20

Original Electronic Certificate

AENOR INTERNACIONAL S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.com